



SKIOLD MOARA DISC

SK2500 / SK5000 / SK10T / SK780



SKIOLD FACE DIFERENTA!

CAPACITATE TONE/ORĂ

Model	SK2500		SK5000			SK10T			SK780	
kW:	5,5	7,5	15	22	30	55	75	90	160	200
Orz:	0,7-1,4	1-1,9	1,7-3,2	2,4-4,7	3-6	5-10	6-13	7-16	9-19,5	12-26
Grâu:	0,75-1,5	1-2	1,8-3,5	2,5-5	3,2-6,5	5-12	6-15	7-18	9-22,5	12-30
Porumb:	0,5-1,5	0,7-2	2-3,5	2,5-5	3-6,5	5-12	6-15	7-18	9-22,5	12-30
Ovăz:	0,6-1	0,8-1,3	1,4-2,3	2-3,2	2,4-4,5	4-9	5-12	6-14	9-18	12-24
Mazăre:	0,5-1,5	0,75-2	2-3,5	2,5-5	3-6,5	4-9	5-12	6-14	9-18	12-24

SPECIFICATII

Model	SK 2500	SK 5000	SK 10T	SK 780
Diametru disc (exterior):	300 mm	450 mm	550 mm	780 mm
Reglare distanta discuri:	Manual sau automat	Manual sau automat	Automat	Automat
Plaja distanta disc:	0 – 15 mm	0 – 15 mm	0 – 8 mm	0 – 9 mm
Dim. interne tubular/pătrat:	Ø100 / Ø150 mm	Ø150 mm	200 x 200 mm	Ø200 mm
Dim. externe, rectangular:	300 x 87 mm	482 x 101 mm	710 x 198 mm	880 x 215 mm
Şnec alimentare:	Opţional (0,37 kW)	Opţional (0,75 kW)	Da (0,75 kW)	Da (1,5 kW)
Ungere rulment principal:	Manual	Manual	Automat	Automat
Întreprupător temperatura:	Nu	Nu	Da	Da
Nivel aprox. zgomot:	80 dB	80 dB	80 dB	80 dB
RPM:	2800	2800	2800	2800
Greutate aprox:	75 kg	175 kg	1100-1400 kg	4250 kg

Cereale uscate si bine curăţate.
Capacitatea depinde de granulaţia de măcinare

